

Screw screw



APPLICATION METHOD :

Screws are used to fasten pipe clamps and various plumbing equipment. Studs are installed in concrete or brick base with dowels.

SPECIFICATION :

- material: high-strength steel;
- surface: galvanized;
- thread type: combined.

Art.	Size	Length, mm	Pieces in a package
0101040319	M6*60	60	1500
0101040318	M6*80	80	1500
0101040320	M8*60	60	1500
0101040306	M8*80	80	1300
0101040301	M8*100	100	1100
0101040302	M8*120	120	850
0101040303	M8*140	140	700
0101040304	M8*160	160	600
0101040305	M8*200	200	500
0101040312	M10*100	100	500
0101040315	M10*120	120	500
0101040316	M10*140	140	500
0101040317	M10*160	160	500
0101040321	M10*200	200	500

Dowel



APPLICATION METHOD :

Universal dowel, for concrete, for lightweight concrete block, for hollow block, for solid block, for stone, granite, for hollow brick, ceramic block, for solid brick.

SPECIFICATION :

- material: polypropylene .

Art.	Size	Length, mm	Pieces in a package
0101040313	10*50	50	1000
0101040309	12*60	60	1000
0101040314	14*80	80	1000

The rod is metric



APPLICATION METHOD :


The metric rod is used for fastening clamps of pipelines and other engineering communications. The metric rod is installed in a concrete or brick base using a collet (mounting spacer anchor).

SPECIFICATION :

- material: high-strength steel DIN 975;
- strength class 4.8;
- surface: galvanized;
- type of thread: metric.

Art.	Size	Length, mm	Pieces in a package
0101040330	M6*1000	1000	50
0101040337	M8*1000	1000	50
0101040338	M8*2000	2000	50
0101040331	M10*1000	1000	25
0101040332	M10*2000	2000	25

Mounting spacer hammering anchor



APPLICATION METHOD :

The dowel is universal, for reinforced concrete, for solid block, for wood, for stone, granite, for solid brick.

SPECIFICATION :

v

Art.	Size	Length, mm	Pieces in a package
0101040342	M6/8x23	23	100
0101040340	m8/10x28	28	100
0101040341	m10/12x32	32	100